

eni Rotra MP ID

eni Rotra MP ID is EP (Extreme Pressure) gear oil recommended for hypoid gears operating under severe conditions and for very highly loaded gears in general, especially those subject to dynamic loads.

It can also be used in conventional gear-boxes and steering -boxes on cars and trucks, and in gear-boxes, final drives and power take-offs on farm and earth-moving machinery.

It can thus be used for lubricating all gears, whatever they are made of, for which the manufacturer recommend an EP lubricant.

CHARACTERISTICS (TYPICAL FIGURES)

eni Rotra MP ID		80W-90	85W-140
SAE Grade		80W-90	85W-140
Appearance	-	B & C	B & C
Density at 15°C	kg/L	0.893	0.908
Viscosity at 100°C	cSt	15.5	27.7
Viscosity at 40°C	cSt	149.0	391.0
Viscosity at -12°C	cP	-	79780
Viscosity at -26°C	cP	143000	-
Viscosity Index	-	107	97
Flash Point COC	°C	192	208
Pour Point	°C	-24	-12

PROPERTIES AND PERFORMANCES

- Its superior EP additives ensure a continuous lubricant film even on gears operating under the severest conditions involving heavy dynamic and shock loads, and very high, or intermittent sliding speeds between the teeth.
- Its outstanding anti-wear properties and its oiliness, markedly reduce gear-tooth and bearing wear.
- Its particularly good oxidation stability prevents any deterioration even when in contact with components operating at high temperatures. Thus any tendency for viscosity to increase or for sludge to form is inhibited. **eni Rotra MP ID** can therefore be kept in use for the long service periods specified by car manufacturers.
- **eni Rotra MP ID** offers good economical improvement in fuel economy by reducing friction plus providing gear components protection against wear, corrosion and costly breakdowns. Its service life is twice or longer than general automotive gear oils.
- **eni Rotra MP ID** is non-corrosive to steel, cooper, and other metals and alloys, and thus helps keep **eni Rotra MP ID** lubricated parts in first-class condition.
- Its antirust properties effectively prevent rust on gears and in bearings even when moisture is present.



eni Rotra MP ID

- Its antifoam qualities minimize the formation of air bubbles which could adversely affect lubricant film continuity.

SPECIFICATIONS

eni Rotra MP ID meets the requirements of the following service and specifications

- API GL-5
- MIL-L-2105D level
- MAN 341 Type M1
- MAN 342 Type N
- ZF TE-ML 07A, 16B, 17B, 19B
- Volvo 97310