

AGIP 4T SUPRA



AGIP 4T SUPRA is designed for lubrication of high power four stroke gasoline motorcycles. The presence of a high viscosity index ensures exceptional thermal and rheological performance in service, while the inclusion of an additive package guarantees for maximum protection of engine even of the most highly rated four stroke motorcycles engines.

CHARACTERISTICS (TYPICAL FIGURES) AGIP 4T SUPRA

Characteristics	ASTM	Unit	SAE GRADE
			20W-50
Density at 15°C	D 4052	kg/l	0.887
Viscosity at 100°C	D 445	mm ² /s	17.6
Viscosity at 40°C	D 445	mm ² /s	151
Viscosity Index	D 2270		129
Flash Point, COC	D 92	°C	230

PROPERTIES AND PERFORMANCES

- AGIP 4T SUPRA is formulated using good quality base stock and has extremely high viscosity index. This is ensuring that the product has exceptional shear resistance, which is essential for correct sump lubrication of four stroke engines.
- Its excellent detergent dispersant characteristics, imparted by careful formulation of the additive package, keep the formation of sludge, varnishes, and deposits completely under control, maintaining all parts of the engine clean and free.
- The entire formulation base oil, additive package and viscosity grade ensures exceptional anti wear and anti corrosion action, guaranteeing maximum engine protection

SPECIFICATIONS

AGIP 4T SUPRA meets the requirements of the following service and specifications:

- API Service SJ
- JASO MA2